

DATA SHEET

TESIRAFORTÉ® DAN VT4

FIXED AUDIO DSP



The TesiraFORTÉ® DAN VT4 is a fixed audio DSP with 32 bi-directional channels of Dante™ digital audio, 4 analog inputs, 4 channels of Acoustic Echo Cancellation (AEC) technology, and 4 analog outputs. It also includes up to 8 channels of configurable USB audio, a 2-channel VoIP interface and a standard FXO telephone interface. USB audio allows TesiraFORTÉ to interface directly with USB audio hosts, as well as to take full advantage of today's most sophisticated conferencing solutions. TesiraFORTÉ DAN VT4 also provides extensive audio processing, including but not limited to: AEC technology, signal routing and mixing, equalization, filtering, dynamics, and delay, as well as control, monitoring, and diagnostic tools; all configured through the Tesira configuration software. TesiraFORTÉ DAN VT4 is best-suited for smaller rooms that require high-quality audio solutions using VoIP, voice lift, mix-minus, and AEC, such as conference rooms or distance learning environments.

BENEFITS

- Integrates VoIP, POTS, and USB audio in one product allowing integrators to choose the type of audio conferencing that works best for their installation
- Includes default configuration file allowing for plug-and-play usage
- Highly scalable and cost-effective solution that can grow over time with the needs of the customer
- SpeechSense™ technology to enhance speech processing
- Integrates directly with soft codecs and other USB audio hosts

FEATURES

- 32 x 32 channels of digital audio networking via the Dante protocol
- 4 mic/line level inputs with AEC, 4 mic/line level outputs
- Gigabit Ethernet port
- Up to 8 channels of configurable USB audio
- RS-232 serial port
- 4-pin GPIO
- 2-line OLED display with capacitive-touch navigation
- Rack mountable (1RU)
- System configuration and control via Ethernet
- Internal universal power supply
- SIP VoIP interface via a RJ-45 connector
- Standard FXO telephone interface via RJ-11 connector
- Signal processing via intuitive software allows configuration and control for signal routing, mixing, equalization, filtering, delay and much more
- CE marked, UL listed, and RoHS compliant
- Covered by Biamp Systems' 5-year warranty

ARCHITECTS & ENGINEERS SPECIFICATION

The fixed audio DSP shall be designed exclusively for use with Tesira® systems. The audio DSP shall support Dante™ digital audio networking that shall allow up to 32 x 32 channels. The Dante networking connection shall be implemented on a RJ-45 connector. The audio DSP shall support Ethernet connection for programming and control on a RJ-45 connector. The audio DSP shall have internal DSP processing. The audio DSP shall include 4 channels of General Purpose Input and Output connection (GPIO) for sending or receiving logic signals. The programming of the GPIO ports shall be software configurable. The audio DSP shall include a RS-232 connection for control data transmission into or out of the audio DSP and such operation shall be software programmable. The audio DSP shall include a Universal Serial Bus (USB) connection on a standard USB-B type connector. The audio DSP shall be software configurable to stream up to 8 channels of digital USB Class 1 Audio transmission either into or out of the audio DSP or simultaneous input and output. The audio DSP shall provide 4 balanced input connections for receiving of microphone or line level analog audio signals on screw-down, removable connectors. The input connections shall include Acoustic Echo Cancellation (AEC) hardware and firmware, the parameters, routing and operation of which shall be software programmable. The audio DSP shall provide 4 balanced output channels for the transmission of microphone or line level analog audio signals on screw-down, removable connectors. Each individual channel shall have its own dedicated connection. The audio DSP shall integrate to Voice Over Internet Protocol (VoIP) systems on a RJ-45 connector for two lines of VoIP communication and shall support Session Initiation Protocol (SIP) v2.0 or later. The audio DSP shall integrate to standard telephony communications on a RJ-11 connector for a single line of telephone communication. The audio DSP shall provide front panel OLED identification of device power, status, alarm, and activity as well as system-wide alarm. The audio DSP shall be rack mountable (1RU) and feature software-configurable signal processing, including but not limited to: signal routing and mixing, equalization, filtering, dynamics, and delay, as well as control, monitoring, and diagnostic tools. The audio DSP shall be CE marked, UL listed, and shall be compliant with the RoHS directive. Warranty shall be five years. The fixed audio DSP shall be TesiraFORTÉ DAN VT4.

TESIRAFORTÉ DAN VT4 SPECIFICATIONS

Frequency Response: 20Hz to 20kHz, +4dBu output:	+0.25 dB/-0.5 dB	Phantom Power:	+48VDC (7mA/input)
THD+N (22Hz to 22kHz): 0dB gain, +4dBu input: 54dB gain, -50dBu input:	< 0.006% < 0.040%	Crosstalk, channel to channel, 1 kHz: 0dB gain, +4dBu input: 54dB gain, -50dBu input:	< -85dB < -75dB
EIN (no weighting, 22Hz to 22kHz):	< -125dBu	Sampling Rate:	48kHz
Dynamic Range (in presence of signal) 22Hz to 22kHz, 0dB gain:	> 108dB	A/D - D/A Converters:	24-bit
Input Impedance (balanced):	8kΩ	Power Consumption: 100-240VAC 50/60Hz:	< 35W
Output Impedance (balanced):	207Ω	USB: Bit Depth: Number of Channels: Sample Rate:	16- or 24-bit up to 8 48kHz
Maximum Input:	+24dBu	Compliance:	FCC Part 15B (USA) FCC Part 68 (USA) Industry Canada CS-03 (Canada) CE marked (Europe) UL und C-UL listed (USA and Canada) RCM (Australia) RoHS Directive (Europe)
Maximum Output (selectable):	+24dBu, +18dBu, +12dBu, +6dBu, 0dBu, -31dBu		
Input Gain Range (6dB steps):	0-66dB		
Overall Dimensions: Height: Width: Depth: Weight:	1.75 inches (44 mm) 19.0 inches (483 mm) 10.5 inches (267 mm) 8 lbs (3.63 kg)		
Environment: Ambient Operating Temperature Range: Humidity: Altitude:	32-104° F (0-40° C) 0-98%, non-condensing 0-6,600 feet (0-2000 Meters) MSL		

TESIRAFORTÉ DAN VT4 BACK PANEL

