

DATA SHEET

VOCIA® VI-6

INPUT DEVICE



The VI-6 is a networked audio input expansion device allowing the user to add up to six channels of audio to a Vocia system. It supports up to six background music inputs, six individual user-configurable paging inputs or four dedicated paging inputs using the Vocia Auxiliary Microphone (VAM-1). The VI-6 features embedded DSP and on-board memory to process and store all device-specific configuration information locally and includes comprehensive, fixed-chain DSP.

FEATURES

- Four sets of dual RCA connectors, plus terminal block connectors for line-level inputs
- Two microphone/line inputs with phantom power
- Four control inputs and four control outputs
- Four auxiliary paging inputs supporting the VAM-1 and VPSI-1
- Software-configurable local audio signal processing, including gain, filters and compressor/limiter
- Rotary switches for unit identification
- CobraNet audio/control with dynamic use of available bundles, plus power over single Ethernet cable
- Status LEDs to indicate signal and clip
- CE marked, UL listed and RoHS compliant
- Covered by Biamp Systems' 5-year warranty

ARCHITECTS & ENGINEERS SPECIFICATION

The audio input device shall be designed exclusively for use with Biamp Vocia systems. It shall be rack mountable (1RU) and provide audio and control via CobraNet.® It shall receive Power over Ethernet (PoE) utilizing a single (CAT5) network cable to a rear panel RJ-45 connector. The audio input device shall provide four sets of dual RCA connectors plus removable terminal block connectors for line-level inputs, two microphone/line inputs with phantom power, four paging inputs, six CobraNet outputs, four control inputs, and four control outputs. The input device shall provide local digital audio signal processing and local storage of configuration data. The input device shall indicate signal and clip with LEDs on the front panel. The input device shall be UL listed, CE marked and shall be compliant with the RoHS directive. Warranty shall be five years. The input device shall be a Vocia VI-6.

VOCIA VI-6 SPECIFICATIONS

Network Connection:	RJ-45 with shielded Ethernet (CAT5, CAT5e, CAT6 or CAT7)	Control Inputs:	
Frequency Response:		Type:	Digital, variable threshold
Line Inputs (20Hz to 20kHz):	± 1dB	Max Input Threshold:	10V
Mic/Line Inputs (35Hz to 20kHz):	± 1dB	Max Input Voltage:	12V
THD + N (20Hz to 8kHz):		Min Input Threshold:	150mV
Line Inputs:	<0.02%	Input Impedance:	100kΩ
Mic/Line Inputs:	<0.05%	Control Outputs:	
Line Inputs Signal-to-Noise Ratio:	>84dB	Type:	Form C Voltage free change over contact
Mic Inputs Equivalent Input Noise:	<-126dBu	Max Operating Voltage:	125VAC, 60VDC
Dynamic Range:	>100dB	Max Switching Capacity:	37VA
Crosstalk (10kHz):	>75dB	Min Operating Load:	10μA @ 10mV DC
Input Impedance:		Power:	802.3af (PoE) Class 3
Line Inputs:	>10kΩ	Environment:	
Mic/Line Inputs:	>1kΩ	Ambient Operating Temperature Range:	23-104° F (-5 - 40° C)
Mic Inputs Phantom Power:	18V behind 3.3kΩ/leg	Humidity:	0 - 95% non-condensing
Overall Dimensions:		Altitude:	0-10,000 Feet (0-3000 Meters) MSL
Height:	1.75 inches (44.5 mm)	Sampling Rate:	48kHz
Width:	19.0 inches (483 mm)	A/D Converters:	24-bit
Depth:	10.0 inches (254 mm)	Compliance:	CE marked (Europe) RoHS Directive (Europe)
Weight:	6.4 lbs (2.9 kg)		

VOCIA VI-6 BACK PANEL

