

Customer Number:

P.O. Number:

P.O. Date:

Ship Via:

Ship Date:

SOLD TO

Name:

Address 1:

Address 2:

City:

State:

Postal Code:

Country:

SHIP TO

Same as SOLD TO

Name:

Address 1:

Address 2:

City:

State:

Postal Code:

Country:

Additional Instructions:

**** ONE CONFIGURATION PER ORDER FORM ****

DSP

(cards are internal to chassis)

DSP-2 (included)
 DSP card with 2 DSPs
 (unit ships with at least 1 card installed, and is included in the unit price)

DSP-2 (optional)
 DSP card with 2 DSPs (up to 2 additional cards can be installed per chassis)

SLOTS 1-13

(optional)

SIC-4
 4 channel mic/line input card

SOC-4
 4 channel mic/line output card

SCM-1
 32x32 CobraNet® module (2 cards max per chassis)
 There is a limit of 3 total network cards (in any combination of AVB-1, SCM-1, and DAN-1) for a single SERVER-IO.

SEC-4
 4 channel mic/line input card with acoustic echo cancellation

STC-2
 2 line POTS interface card
 There is a limit of 6 total telephony cards (in any combination of STC-2 and SVC-2) for a single SERVER-IO.

DAN-1
 64x64 Dante™ interface card (2 cards max per chassis)

SAC-4
 4 channel mic/line input card with ambient noise compensation

SVC-2
 2 line VoIP card

Total Quantity of Input/Output Cards
 (13 cards max per chassis)

Total Quantity of Units with Above Configuration

*The unit ships from the factory with an SNC-1 card already installed in Slot 14, which is included in the unit price. This card is required for proper unit operation.

*Slot 13 is a "Super I/O" slot, which can only accept an SCM-1 or DAN-1 card in this configuration.

