# Desono™
# Ceiling Loudspeaker Accessories
# New Construction Bracket
## Installation Guide

Biamp offers New Construction Brackets (NC) suitable for all Desono CM, C-IC6 and D Series ceiling loudspeakers. The illustrations below are a typical installation in a drywall ceiling. Please refer to the appropriate Installation and Operation guide for additional information on drywall ceiling installation methods, and preinstallation in a new drywall ceiling.

**New Construction Bracket**

## Installation

1. Fasten the bracket to the trusses. Run wire(s) to the location and secure them to the top of the bracket. B-style brackets have cleats to easily secure the wiring with cable ties before ceiling is installed - see box below

   **Note:** Use of a stretched string or laser to align the brackets, rather than aligning to the truss is recommended.
2. Install drywall.
3. Cut out the hole.
4. Install ceiling loudspeaker after the ceiling is finished following installation guide for that model.

| Model | Fits | Style |
|---|---|---|
| SPA-NC100 | CM20DTS, CM30DTD | B |
| SPA-NC200 | CM60DTD | B |
| D45-NCB | D4LP, D4, D5 | A |
| D6-NCB | D6, D6-B, C-IC6 | A |
| D8-NCB | D8 | A |
| D10-NCB | D10, D10SUB | A |

*Typical C-IC6 installation in drywall ceiling*

A: 9300 S.W. Gemini Drive Beaverton, OR 97008 USA W: www.biamp.com

# TECHNICAL DRAWINGS

## SPA-NC100 / SPA-NC200

Exterior dimensions and hole placement are shared on the 3 drawings at left. The ID of the hole cutout is noted for each model.

### SPECIFICATIONS

**Material / Finish:** 1 mm steel. / Bright zinc plate
**Quantity per Kit:** Sold in 6-packs

## D45-NCB / D6-NCB

Scan this QR-code and navigate to your loudspeaker model to download the appropriate installation guide

bia.mp/DesonoCeiling_pubs

## D8-NCB / D10-NCB

*Drawings not to scale*

### CONTACT US

Email: support@biamp.com
Web: support.biamp.com
Warranty: biamp.com/legal/warranty-information