


DATA SHEET

IMPERA OSCAR

4-BUTTON CONTROL PAD WITH ETHERNET PORT



The 4-button Impera Oscar control pad is a compact, highly customizable AV control suitable for wall-mounting or installation in the EasyConnect tabletop cable management solution. It provides a simple and intuitive interface for presentation spaces, learning environments, and conference rooms, regardless of the type of equipment installed.

The Oscar can be quickly programmed and customized within Project Designer as the needs of the room change over time, making it a very flexible and cost effective control solution.

FEATURES

- Supports up to 4 software-configurable buttons
- Includes on-board controller; no external processor required
- 1 bi-directional RS-232/IR port for third party control with feedback
- 2 GPIO ports
- Mini USB connection for system configuration and maintenance
- Supports email notifications for lamp/filter hours and warnings
- Covered by Biamp Systems' five-year warranty

ARCHITECTS & ENGINEERS SPECIFICATION

The control pad shall include 4 mechanical buttons for initiating control functions. The control pad shall include 4 multicolor, software configurable LEDs. Each mechanical button shall have a corresponding LED. The control pad shall utilize an Ethernet network via an RJ-45 connector for networking as well as software configuration and control. The control pad shall include 1 bi-directional RS-232/IR port for controlling third party devices with feedback functionality and shall be software programmable. The control pad shall include 2 channels of General Purpose Input and Output connection (GPIO) for sending or receiving logic signals. The programming of the GPIO ports shall be software configurable. The control pad shall be CE marked and shall be compliant with the RoHS directive. Warranty shall be five years. The control pad shall be the Impera Oscar.

IMPERA OSCAR SPECIFICATIONS

Control Button Quantity: 4 Button Type: Mechanical LED Indicators: Multi-color		EU Model Dimensions Height: 2.2 inches (55 mm) Width: 2.2 inches (55 mm) Depth: 0.9 inches (24 mm)	
Ethernet Port Speed: 10/100 Mbps Autosense: Yes		DK Model Dimensions Height: 1.8 inches (45 mm) Width: 2.8 inches (72 mm) Depth: 0.9 inches (24 mm)	
GPIO I/O Quantity: 2 Sense Low: < 1 VDC Sense High: > 4 VDC Output Type: Open drain Max Voltage: 24 VDC Max Current: 0.5 A		Weight: 0.20 lbs (90 g)	
RS-232 / IR Number of Ports: 1 (bidirectional) Baud Rate: 1200 - 115200 bit/sec Data Bits: 7, 8 Parity: Even, Odd, None Stop Bits: 1, 1.5, 2 IR Frequency Range: 381 Hz to 500 kHz		Environmental Ambient Operating Temperature Range: 32 - 104° F (0 - 40° C) Humidity: 10-90% relative humidity (non-condensing) Altitude: 0-6,600 ft (0-2000m) MSL	
Power: 12V DC 5W		Compliance CE Marked (Europe) RoHS Directive (Europe)	

IMPERA OSCAR REAR PANEL (EU MODEL)



IMPERA OSCAR MODELS

4DKW	DK form factor, white
4DKB	DK form factor, black
4EUW	EU form factor, white
4EUB	EU form factor, black

Biamp and Impera are either trademarks or registered trademarks of Biamp Systems, LLC in the United States and other countries. Other product names referenced may be trademarks or registered marks of their respective owners and Biamp Systems is not affiliated with or sponsored by these companies.