

DATA SHEET

QT® ACTIVE EMITTER SOUND MASKING EMITTER

MODEL NUMBER: E-P-W (WHITE), E-P-B (BLACK)



Qt® Active Emitters are wide dispersion (nearly 180 degrees) direct field devices with 1.25" (3.17 cm) drivers capable of simultaneous reproduction of both sound masking and clear audio sources such as paging signals. Patented direct-field technology ensures both uniform, comfortable sound masking as well as clear, articulate paging in a device that's virtually invisible once deployed in finished or open structure ceilings. The Qt Active Emitter features onboard active electronics to power the emitter and a ported enclosure design allowing lower frequency extension to the 100 Hz octave band. Power is delivered via an external power supply and power injectors, both available as accessories. Active Emitters deliver four uncorrelated audio channels, automatically eliminating phasing. Active Emitters are plenum-rated, ETL listed, and comply with UL 2043. Each Active Emitter comes standard with a slip-ring mount for acoustical tile mounting. These features, along with plug and play installation and easy configuration capability, make Cambridge Qt® X systems the most intelligently engineered and most effective sound masking systems on the market today.

FEATURES

- Wide dispersion direct field drivers with 1.25" (32 mm) drivers
- Small driver size results in nearly 180° dispersion of direct field sound masking
- Reduces acoustical interference by using four uncorrelated channels
- DIP switches attenuate the volume level up to 4.5 dB in 1.5 dB decrements for easy micro-zoning
- Plug and play installation and easy configuration
- Comes standard with slip ring for acoustical tile mounting
- CE marked, ETL listed, and RoHS compliant
- Evaluated to the requirements of UL 2043 and is suitable for use in air handling spaces
- Covered by Biamp Systems' five-year warranty

ARCHITECTS & ENGINEERS SPECIFICATION

The emitter shall consist of a single 1.25" (32 mm), 40KΩ, full range driver installed in a vented enclosure. The enclosure shall be manufactured from material meeting UL Standard 2043 requirements for heat and smoke release in accordance with the provisions of the following codes: National Electric Code, NFPA 70; International Mechanical Code, NFPA 5000; Standard for the Installation of Air Conditioning and Ventilating Systems, and NFPA 90A. The emitter shall be provided with internal logic to automatically sequence 4 channels of mutually incoherent masking sound generators when connected with standard category cables. Input and output receptacles shall be standard RJ-45 quick connect network type with positive locking. A twist-and-lock mounting ring shall be provided for quick and secure mounting in ceiling materials. The enclosure shall provide a secondary attachment for a security cable where required by local authorities. Warranty shall be 5 years. The emitter shall be a Qt® Active Emitter.


Biamp, Cambridge, Qt, and QtPro are either trademarks or registered trademarks of Biamp Systems, LLC in the United States and other countries. Other product names referenced may be trademarks or registered marks of their respective owners and Biamp Systems is not affiliated with or sponsored by these companies.

Qt ACTIVE EMITTER SPECIFICATIONS


Emitter Type:	Active with integrated amplifier	Maximum Power Consumption:	2 W
Frequency Response		Driver Diameter:	1.25" (32mm)
Sound Masking¹:	100Hz to 6.8kHz	Enclosure:	Front Vented
Music/Paging:	105Hz to 12kHz	Color:	Black or White
SPL¹		Product Dimensions	
Minimum Masking SPL (@ 1m):	30dBA	Overall Diameter:	3.25 inches (83mm)
Maximum Masking SPL (@ 1m):	60dBA	Depth:	3.5 inches (89mm)
Maximum Music/Paging SPL (@ 1m):	74dBA	Weight:	6.5 oz. (184g)
Nominal Impedance:	40 kΩ	Installation Cutout Diameter:	2.68 inches (68mm)
Nominal Dispersion:	170° conical / half space	Included Accessories:	Acoustic Ceiling Tile Mounting Ring UTP Cable (16ft/25ft/30ft)
Channel Selection:	4 Auto-Sequencing and Repeating Channels	Compliance:	ETL listed (USA and Canada) Evaluated to the requirements of UL 2043 and is suitable for use in air handling spaces
Selectable Attenuation:	0 dB, -1.5 dB, -3 dB, -4.5 dB		
I/O Connectors:	2 RJ-45 connectors		
Cabling:	Category UTP Cabling (8 conductor)		

¹ Specifications based on emitter array using published layout practices in conjunction with Qt Control Processor.


FREQUENCY RESPONSE (dB SPL)



BEAMWIDTH (Degrees)



DIMENSIONS



REQUIRED ACCESSORIES

Description	SKU
Power Supply	PS-AE-3
Power Injector	PI-AE

OPTIONAL ACCESSORIES

Description	SKU
Drywall Mount	DM
Beam Bracket	AE-BB-W, AE-BB-B
Universal Bracket	AE-UB-W, AE-UB-B