



## **Desono C-IC6LP-TAA A&E Specifications**

**C-IC6LP-TAA:** The loudspeaker system shall be a two-way, full-range ceiling mount system with a 6.5-inch (165 mm) low frequency transducer and a coaxially mounted 1.0-inch (25mm) exit high frequency compression driver. The drivers shall be connected to an integral crossover with a crossover frequency of 2.5 kHz, with a self-resetting solid state circuit breaker for driver protection. The loudspeaker baffle shall be constructed of UL 94V-0 rated ABS material and include three patent-pending SpringLock™ mounting clamps with 1.3-inch (33 mm) grip range to support the back can on the included tile rails and C-ring, so that the installer no longer needs to hold the can against the tile while tightening the clamps. A powder-coated perforated steel grille with either white or black finish backed with color matched woven fabric shall be included.

The system shall have an operating range of 63 Hz to 20 kHz and a low impedance (8 ohm) input capability of 22V. The sensitivity on-axis, referenced to a distance of 1 meter, and an input voltage of 2.83V shall be 87dB. The loudspeaker system shall have a conical coverage pattern of 145 degrees. The nominal system impedance shall be 8 ohms (in low impedance setting).

The loudspeaker shall be equipped with a four-position, 5.08 mm (0.2 inches) pluggable Euroblock connector and two RJ-45 connectors for audio signal connections. The loudspeaker shall include mounting points for direct attachment of a Tesira® AMP-450BP amplifier.

A C-Ring supporting plate and two tile support bridge rails shall be included. The loudspeaker system shall have a bezel diameter of 13.1 inches (333mm), a can depth of 3.96 inches (101mm) and weigh 9.1 lbs (4.12 kg). There shall be an optional New Construction Bracket for installing the loudspeaker system in new construction before drywall or plaster is put into place. An optional pair of 48-inch (1219mm) tile rails shall also be available to mount the loudspeaker in larger ceiling grids. Optional multi-pack accessories also include black grilles for black ceiling installations or high humidity grilles for coastal installations.

The system shall be ETL listed to comply with UL1480, UL2043 and CSA62368-1 and suitable for use in air handling spaces per NFPA70 and NFPA90. The loudspeaker shall be UL listed, CE marked, and shall be compliant with the RoHS directive. The loudspeaker shall comply with the United States Trade Agreement Act (TAA). The loudspeaker system shall be a Desono C-IC6LP-TAA.